

Technology Parameter

Technology Parameter

| Rated current (Ith) | 16 | 20 | 25 | 32 | 40 | 50 | 63 | 80 | 100 | 125 | 160 | 250 | 400 | 630 | 800 | 1000 | 1250 | 1600 | 2000 | 2500 | 3200 | | | | | | | | | | |
|---|-----------------------|----|----|----|----|----|--------|----|------|-----|------|-----|------|-----|---------|------|------|------|------|------|------|------|----|--|------|--|----|--|----|--|----|
| Rated insulation voltage (Ui) | 500V | | | | | | | | | | | | | | 800V | | | | | | | | | | | | | | | | |
| Rated concussion withstand voltage (Uimp) | 6KV | | | | | | | | | | | | | | 8KV | | | | | | | | | | | | | | | | |
| Rated working voltage (Ue) | AC400V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rated working current(Ie) | 16 | 20 | 25 | 32 | 40 | 50 | 63 | 80 | 100 | 125 | 160 | 250 | 400 | 630 | 800 | 1000 | 1250 | 1600 | 2000 | 2500 | 3200 | | | | | | | | | | |
| Using classes | AC-33B | | | | | | | | | | | | | | AC-33iB | | | | | | | | | | | | | | | | |
| Rated limited shortcircuit current (Is) | 8kA | | | | | | | | 26kA | | | | | | | 67kA | | | | | | | | | | | | | | | |
| Rated short-time withstand current (Is) | 5kA | | | | | | 12.6kA | | | | | | | | | 32kA | | | | | | | | | | | | | | | |
| Transfer I - II or II - I | 2s | | | | | | 0.6s | | | | | | | | | 1.2s | | | 1.8s | | | 2.4s | | | | | | | | | |
| Control power voltage | DC24V、48V、110V、AC220V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Rated frequency | 300W | | | | | | | | 325W | | 355W | | 400W | | 440W | | | | 600W | | | | | | | | | | | | |
| Start Normal | 55W | | | | | | | | 62W | | 74W | | 90W | | 98W | | | | 120W | | | | | | | | | | | | |
| Weight(kg) 4 pole | 3.4 | | | | | | | | 6.0 | | 6.0 | | 7.6 | | 15.8 | | 16.8 | | 36 | | 36 | | 37 | | 38.6 | | 55 | | 61 | | 67 |